

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(43) International publication date

29 April 2004 (29.04.2004)

PCT

(10) International publication number

WO 2004/035248 A1

(51) International patent classification⁷:

B22D 11/115

(72) Inventor; and

(21) International application number:

PCT/FR2003/002978

(75) Inventor/Applicant (US only): IKUNSTREICH, Siebo
[FR/FR]; 27, rue Eugène Berthoud, F-93400 Saint-Ouen (FR).

(22) International filing date:

9 October 2003 (09.10.2003)

(74) Representative: VENTAVOLI, Roger; Rove Conseils,
47, rue de Paris, Boîte postale 50 229, F-57106
Thionville Cedex (FR).

(25) Language of filing:

French

(26) Language of publication:

French

(30) Data relating to the priority:

02/12,706

14 October 2002 (14.10.2002)

FR

(81) Designated states (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(71) Applicant (for all designated States except US): ROTTELEC
[FR/FR]; Tours Mercuriales, 40, rue Jean Jaurès, F-93170
Bagnolet (FR).

[continued on next page]

As printed

(54) Title: METHOD AND DEVICE FOR CONTROLLING FLOWS IN A CONTINUOUS SLAB-CASTING INGOT MOULD

(54) Titre : PROCEDE ET DISPOSITIF POUR LA MAITRISE DES ECOULEMENTS DANS UNE LINGOTIERE DE COULEE CONTINUE DE BRAMES



WO 2004/035248 A1

(57) Abstract: The invention concerns a continuous casting ingot mould equipped with an immersed nozzle (3) provided with lateral outlets (2) opposite the small sides (5) of the ingot mould, and whereof the pattern of molten metal flows can be naturally in single loop or double loop, or even unstable. The invention is characterized in that it consists in using sliding magnetic fields acting, at the nozzle, on the flows of liquid metal reaching the ingot mould through the nozzle orifices, said magnetic fields being generated by polyphase linear electromagnetic field windings (14, 14', 15, 15') arranged opposite at least one side of the ingot mould on either side of the nozzle, preferably opposite one large side and advantageously both, so as to set, or stabilize, a permanent pattern in double loop mode.

[continued on next page]